

U.S.S.N. 10/658,708

Claim Amendments

Please amend claims 1, 11, and 21-28 as follows:

U.S.S.N. 10/658,708

Listing of Claims

1. (currently amended) An apparatus for dispensing a liquid onto a substrate frontside and backside during a development process and adjustably controlling liquid flow on said substrate backside during said development process to improve a rinsing step, comprising:

a support for receiving the substrate;

a dispensing head for dispensing the liquid onto the substrate;

a knife ring having a base and a tapered edge
comprising an upper edge of said knife ring extending from said base, said knife ring vertically adjustably mounted beneath said support to position said knife ring upper edge adjacent said substrate backside; and

a plurality of independently-actuated automatic vertical adjustment mechanisms operably engaging said base of

U.S.S.N. 10/658,708

said knife ring for placing said knife ring upper edge at selected vertical positions ~~beneath the~~ adjacent said substrate backside during said development process.

2. (previously presented) The apparatus of claim 1 wherein said plurality of independently-actuated automatic vertical adjustment mechanisms comprise a plurality of fluid-actuated ring actuating cylinders.

3. (previously presented) The apparatus of claim 1 wherein said knife ring has a diameter of about 290 mm.

4. (previously presented) The apparatus of claim 3 wherein said plurality of independently-actuated automatic vertical adjustment mechanisms comprise a plurality of fluid-actuated ring actuating cylinders.

5. - 6. (Canceled)

7. (previously presented) The apparatus of claim 2 wherein said plurality of fluid-actuated ring actuating cylinders is actuated by pneumatic pressure.

U.S.S.N. 10/658,708

8. (previously presented) The apparatus of claim 7 wherein said knife ring has a diameter of about 290 mm.

9. - 10. (Canceled)

11. (currently amended) An apparatus for dispensing a liquid onto a substrate frontside and backside during a development process and adjustably controlling liquid flow on said substrate backside during said development process to improve a rinsing step, comprising:

a support for receiving the substrate;

a dispensing head for dispensing the liquid onto the substrate;

a knife ring having a base and a tapered edge
comprising an upper edge of said knife ring extending from said base, said knife ring vertically adjustably mounted beneath said support to position said knife ring upper edge adjacent said substrate back side; and

U.S.S.N. 10/658,708

a pair of independently-actuated hydraulic-powered ring actuating cylinders operably engaging said base of said knife ring in generally diametrically-opposed relationship to each other for placing said knife ring upper edge at selected vertical positions ~~beneath the~~ adjacent said substrate backside during a development process.

12. (previously presented) The apparatus of claim 11 wherein said knife ring has a diameter of about 290 mm.

13. - 20. (Canceled)

21. (currently amended) The apparatus of claim 1, wherein said vertical positions are ~~selectable~~ from a position facilitating flow of liquid between said knife ring upper edge and said substrate backside and a position substantially preventing a flow of liquid between said knife ring upper edge and said substrate backside.

22. (currently amended) The apparatus of claim 21, wherein said position facilitating flow of liquid between said knife ring upper edge and said substrate backside comprises a gap distance

U.S.S.N. 10/658,708

between ~~an upper edge of~~ said knife ring upper edge and said substrate backside of about 1.4 mm to about 1.4 mm.

23. (currently amended) The apparatus of claim 21, wherein said position substantially preventing flow of liquid between said knife ring upper edge and said substrate backside comprises a gap distance between an ~~upper edge of~~ said knife ring upper edge and said substrate backside to prevent said liquid flow while said substrate is rotating.

24. (currently amended) The apparatus of claim 21, wherein said position substantially preventing flow of liquid between said knife ring upper edge and said substrate backside comprises a gap distance between an ~~upper edge of~~ said knife ring upper edge and said substrate backside of about 0.1 mm to about 0.4 mm.

25. (currently amended) An apparatus for dispensing a liquid onto a substrate frontside and backside during a development process and adjustably controlling liquid flow on said substrate backside during said development process to improve a rinsing step, comprising:

a support for receiving the substrate;

U.S.S.N. 10/658,708

a dispensing head for dispensing the liquid onto the substrate;

a knife ring having a base and a tapered edge comprising an upper edge of said knife ring extending from said base, said knife ring vertically adjustably mounted beneath said support to position said knife ring upper edge adjacent said substrate backside; and

a plurality of independently-actuated automatic vertical adjustment mechanisms operably engaging said base of said knife ring for placing said knife ring upper edge at selected vertical positions ~~beneath the~~ adjacent said substrate backside during said development process;

wherein said vertical positions are selectable ~~from~~ from a position facilitating flow of liquid between said knife ring upper edge and ~~[[a]]~~ said substrate backside and a position substantially preventing flow of liquid between said knife ring upper edge and said substrate backside.

U.S.S.N. 10/658,708

26. (currently amended) The apparatus of claim 25, wherein said position facilitating flow of liquid between said knife ring upper edge and said substrate backside comprises a gap distance between ~~[[an]] upper edge of said knife ring~~ upper edge and said substrate backside of about 1.4 mm to about 1.4 mm.

27. (currently amended) The apparatus of claim 25, wherein said position substantially preventing flow of liquid between said knife ring upper edge and said substrate backside comprises a gap distance between ~~an upper edge of said knife ring~~ upper edge and said substrate backside of about 0.1 mm to about 0.4 mm.

28. (currently amended) The apparatus of claim 25, wherein said position substantially preventing flow of liquid between said knife ring upper edge and said substrate backside comprises a gap distance between ~~[[an]] upper edge of said knife ring~~ upper edge and said substrate backside to prevent said liquid flow while said substrate is rotating.

29. (previously presented) The apparatus of claim 25 wherein said plurality of independently-actuated automatic vertical adjustment mechanisms comprise a plurality of fluid-actuated ring actuating

U.S.S.N. 10/658,708

cylinders.

30. (previously presented) The apparatus of claim 29 wherein said plurality of fluid-actuated ring actuating cylinders is actuated by pneumatic pressure.

31. (previously presented) The apparatus of claim 25 wherein said knife ring has a diameter of about 290 mm.